



protects against dust, dirt and paint

Stokvis Tapes Quick Masking

TAPE & COVER UP

Quick Masking: pre-taped plastic foil

avoid extra costs for cleaning, repair and/or replacement due to damage

Strong, pre-folded transparent PE-foil or brown paper foil. Provided with a self-adhesive masking tape on one side. The solution for effortlessly protecting, covering and masking large surfaces in one go. Quick Masking protects against dust, dirt and paint.

Quick Masking:

- is a must-have during construction, renovation, painting, cleaning, etc;
- is suitable for large surfaces, such as doors, furniture, walls, windows, etc;
- can also be used for masking large surfaces when refinishing vehicles;
- the statically charged film attracts spray mist and dust;
- adheres itself to substrates due to the static charge;
- is ideal for taping along straight lines.



Available at Stokvis Tapes!

professional displays for your self-adhesive tapes

Organise your products just like you want it. Devote one of your displays for example to painting jobs by stacking several masking tapes and Quick Masking in your display (see image).

Stokvis' displays: the best way to draw attention to your tape products.





TMP - Quick Masking Standard

the best choice for a short-term project on an irregular surface

- can be used indoors
- can be used outdoors, remove immediately after outdoor use
do not expose to sunlight (not UV-resistant)
- can be removed cleanly from most common substrates for up to 2 days
- good adhesion, even on irregular surfaces
- masking tape color: cream
- adhesive layer: rubber
- total thickness: 0.13mm
- PE-foil thickness: 6µm



A crepe paper masking tape: the paper version is tear able by hand. A separate dispenser is available for quick and easy cutting of the PE-film into the right size during application.

Specifications	Product description	Dimensions	Color
	TMP55033 General masking pretaped protection film	550mm x 33m MASK IND	cream
	TMP270017 General masking pretaped protection film	2700mm x 17m MASK IND	cream



TMP BL - Quick Masking UV

the right choice for large, irregular surfaces both indoors and outdoors

- can be used outdoors and indoors: UV-resistant
- medium adhesive strength, even on irregular surfaces
- can be removed cleanly from most common surfaces for up to 14 days
- masking tape color: blue
- adhesive layer: rubber
- total thickness: 0.13mm
- PE-film thickness: 6µm



A separate dispenser is available for quick and easy cutting of the PE-film into the right size during application.

Specifications	Product description	Dimensions	Color
	TMP140020BL UV masking pretaped protection film	1400mm x 20m OUT	blue
	TMP270017BL UV masking pretaped protection film	2700mm x 17m OUT	blue



TMP WA - Quick Masking Washi

the right choice for a long lasting (paint) job on a smooth surface

- can be used indoors and outdoors: UV-resistant
- average adhesive strength, suitable for smooth surfaces
- ideal for painted, glass and metal surfaces
- can be removed cleanly from most common surfaces for up to 60 days
- Correct use of this masking protective results in sharp paint edges
- masking tape color: yellow
- adhesive layer: acrylic
- total thickness: 0.08mm
- PE-film thickness: 6µm



A separate dispenser is available for quick and easy cutting of the PE-film into the right size during application.

Specifications	Product description	Dimensions	Color
	TMP140033WA Washi pretaped protection film	1400mm x 33m Washi	yellow
	TMP270017WA Washi pretaped protection film	2700mm x 17m Washi	yellow



TMP CT - Quick Masking Duct

the right choice for rough surfaces indoors and outdoors

- can be used indoors and outdoors: UV-resistant
- can be removed cleanly for up to 14 days, depending on the surface
- easy to tear with a dispenser
- high adhesive strength for adhesion on rough surfaces
- color duct tape: blue
- adhesive layer: rubber
- total thickness: 0.13mm
- PE-film thickness: 15µm



A separate dispenser is available for quick and easy cutting of the PE-film into the right size during application.

Specifications	Product description	Dimensions	Color
	TMP240018CT Duct pretaped protection film	2400mm x 18m DUC OUT	blue



IMPORTANT NOTES

achieve the best result

- All substrates should be clean and contamination free and the tape should be applied with pressure.
- Removability of the product depends on the surface and how long it remains applied. Do not leave the tape on longer than necessary.
- When using Quick Masking for painting: remove the tape immediately after the paint has dried.
- Alle genoemde Quick Masking producten in deze brochure kunnen functioneren tussen -10 en 50 °C. De Quick Ducttape masking kan zelfs nog bij -35 °C functioneren.
- All mentioned Quick Masking products in this brochure can operate between -10° and 50°C. The Quick Duct Masking can even function at -35°C.
- All Quick Masking products mentioned in this brochure can be stored for up to one year provided they are stored at room temperature in their original packaging and out of direct sunlight.
- Please read the specifications of the Quick Masking products carefully. Choose the right tape for your application. In doubt? Your Tape Specialist will be happy to help.

Each user must test the suitability of the product for its intended use and bears all risk and liability in connection therewith. Stokvis Tapes shall not be liable for any damage resulting from the unsuitability of the product.

Masking Tapes

In addition to Quick Masking, we also carry various masking tapes in our range. On this page an overview of our standard products.


M451 - Paper masking tape Standard

the right choice for a short-term job on an (un)regular surface

- can be used indoors
- can be used outdoors, remove immediately after outdoor use
do not expose to sunlight (not UV-resistant)
- can be removed without leaving any adhesive residue on most common substrates, immediately after the paint has dried
- good adhesion, even on irregular surfaces
- strong and conformable
- masking applications at temperatures <80°C (max 30min at 80°C)
- masking tape color: cream
- adhesive layer: rubber
- total thickness: 0.125mm



Specifications	Product description	Dimensions	Color
	M451 Maskingtape 0.125 80°C (30min)	19mm x 50m	cream
	M451 Maskingtape 0.125 80°C (30min)	25mm x 50m	cream
	M451 Maskingtape 0.125 80°C (30min)	38mm x 50m	cream
	M451 Maskingtape 0.125 80°C (30min)	50mm x 50m	cream



126500 YE – Professional ultra-thin masking tape made of strong and flexible Washi paper

the right choice for very high-quality masking and painting work without paint or varnish creep and razor-sharp edges

- indoor and outdoor use: good UV-resistance
- medium adhesive strength, also suitable for smooth surfaces
- temperature resistant up to 120°C
- can be removed cleanly from most common surfaces for up to 60 days outdoors
- clean removable from most common surfaces up to 120 days indoors
- correct use of this Washi masking tape results in razor-sharp paint edges
- masking tape color: yellow
- adhesive layer: acrylic
- total thickness: 0.09mm



Specifications	Product description	Dimensions	Color
	126500 YE BAR Washi masking tape 0.09 120°C	19mm x 50m	yellow
	126500 YE BAR Washi masking tape 0.09 120°C	25mm x 50m	yellow
	126500 YE BAR Washi masking tape 0.09 120°C	38mm x 50m	yellow
	126500 YE BAR Washi masking tape 0.09 120°C	50mm x 50m	yellow



128500 VI – Professional low tack adhesive ultra-thin masking tape from Washi paper

the right choice for very high-quality masking and painting work, with razor-sharp edges and excellent removability from the most delicate surfaces

- can be used indoors
- low tack and adhesion, especially suitable for delicate surfaces such as wallpaper
- also suitable for fresh, fully dried paint coats
- temperature resistant up to 60°C
- can be removed cleanly from most common surfaces for up to 60 days indoors
- correct use of this Washi masking tape results in sharp paint edges
- masking tape color: violet
- adhesive layer: acrylic



Specifications	Product description	Dimensions	Color
	128500 VI BAR Washi masking tape 0.08 60°C	19mm x 50m	violet
	128500 VI BAR Washi masking tape 0.08 60°C	25mm x 50m	violet
	128500 VI BAR Washi masking tape 0.08 60°C	38mm x 50m	violet
	128500 VI BAR Washi masking tape 0.08 60°C	50mm x 50m	violet





Belgium

China

Denmark

Germany

Finland

France

India

Italy

Mexico

Netherlands

Norway

Poland

Portugal

Russia

Spain

Czech Republic

United Kingdom

United States of America

Sweden

STOKVIS TAPES BENELUX BV
21/05/2021

Belgium

Mechelsesteenweg 586C

1800 Vilvoorde

Email: info@stokvistapes.be

Tel. +32 (0)22 55 06 11

Netherlands

Van Hennaertweg 10

2952CA Alblasterdam

Email: info@stokvistapes.nl

Tel. +31 (0)78 699 21 00