

Self-adhesive solutions for door and window frames

Doors and windows are an essential part of any building. Draught excluder contributes to a comfortable indoor environment because:

- it reduces energy consumption;
- it prevents heat loss and draughts inside;
- keeps dust and pollen out;
- it reduces noise from outside.

EPDM DRAUGHT EXCLUDER (SELF-ADHESIVE)

Self-adhesive extruded EPDM rubber draught excluders for doors and windows are:

- easy and quick to install;
- can be used indoors;
- very flexible;
- lifetime >8 years.

E-profile fits into gaps of 1.5 - 3.5mm. P-profile fits into gaps of 2 - 5mm. All-round profile fits into gaps of 2 - 7.5mm.















	Product description	Dimensions	Thickness	Color	Minimum order quantity
	TLP9556BR/WH EPDM draught excluder P-profile self-adhesive	9mm x 6mtr	5.5mm	• 0	12 rolls (1 carton)
	TLP95524BR/WH EPDM draught excluder P-profile self-adhesive	9mm x 24mtr	5.5mm	• 0	9 rolls (1 carton)
	TLP100BR EPDM draught excluder P-profile self-adhesive	9mm x 100mtr	5.5mm	•	8 rolls (1 carton)
	TLP100WH EPDM draught excluder P-profile self-adhesive	9mm x 100mtr	5.5mm	0	8 rolls (1 carton)
	TLE9556BR/WH EPDM draught excluder E-profile self-adhesive	9mm x 6mtr	4mm	• 0	12 rolls (1 carton)
	TLE95524BR/WH EPDM draught excluder E-profile self-adhesive	9mm x 24mtr	4mm	• 0	9 rolls (1 carton)
	TLE100BR/WH EPDM draught excluder E-profile self-adhesive	9mm x 100mtr	4mm	• 0	8 rolls (1 carton)
LUDERS	TLA1582BA EPDM all-round draught excluder self-adhesive	15mm x 2mtr	8mm	•	12 rolls (1 carton)
EPDM DRAUGHT EXCLUDERS	TLA1055BA EPDM all-round draught excluder self-adhesive	10mm x 5mtr	5mm	•	12 rolls (1 carton)
	TLA105100BA EPDM all-round draught excluder self-adhesive	10mm x 100mtr	5mm		8 rolls (1 carton)

THERMOPLAST DRAUGHT EXCLUDER (SELF-ADHESIVE)

Self-adhesive thermoplastic draught excluders with Omega profile are:

- suitable for doors and windows;
- resistant to all weather conditions;
- suitable for gaps of 1 6.5mm;
- flexible;
- waterproof;
- washable;
- applicable inside and outside;
- lifespan of >15 years.

















		Product description	Dimensions	Thickness	Color	Minimum order quantity
THERMOPLAST DRAUGHT EXCLUDERS	0.	TLTPOM6 BA/TR/WH Thermoplast draught excluder self-adhesive Omega profile	9mm x 6mtr	7mm	● ® ○	12 rolls (1 carton)
	0	TLTPOM24 BA/TR/WH Thermoplast draught excluder self-adhesive Omega profile	9mm x 24mtr	7mm	● ® ○	8 rolls (1 carton)
	S. C.	TLTPOM100TR Thermoplast draught excluder self-adhesive Omega profile	9mm x 100mtr	7mm	®	8 rolls (1 carton)
	0.	TLTPOM100WH Thermoplast draught excluder self-adhesive Omega profile	9mm x 100mtr	7mm	0	8 rolls (1 carton)

SILICONE DRAUGHT EXCLUDER

Non-adhesive silicone draught excluders for doors and windows protect against cold, draughts, heat, moisture, dust and pollen, thereby helping to save energy. The strips are flexible, waterproof and washable. They can be used outdoors and are UV-resistant. Silicone draught excluders have a lifespan of >15 years.

Omega profile draught excluder, suitable for gaps of 3 - 7 mm. P-profile draught excluder, suitable for gaps of 3 - 7.5mm.

















S
UDERS
Ш
\dashv
SILICONE DRAUGHT EXCLI
\sim
ш
IGHT E)
王
9
\Rightarrow
~
\overline{a}
100
=
\overline{c}
<u>ರ</u>
===

	Product description	Dimensions	Thickness	Color	Minimum order quantity
0.	KLW71000MEGA Silicone Omega profile non-adhesive	7mm x 100mtr	7mm	0	6 rolls (1 carton)
	KLW75100WH Silicone Omega profile non-adhesive	7.5mm x 100mtr	7.5mm	0	6 rolls (1 carton)

PROTECTIVE FOILS

avoid extra costs for cleaning, repair and/or replacement due to damage

During manufacturing, transport and construction work, you want to avoid extra costs due to damage as much as possible. For doors and windows, we have protective tapes and films that combine excellent mechanical protection with residue-free removal. Here it is important that the right tape is applied and removed correctly. Please consult your tape specialist to find out which tape is best suited for your application and how to apply and remove the tape correctly.

Please note that protective foils must first be tested on the substrate itself. Be extra careful with porous paints and natural stone substrates.



		Product description	Dimensions complete r	oll Thickness	Color	Minimum order quantity	
		129222 1250mm x 200m PE protective film with self-adhesive rubber layer for indoor applications is excellent cleanly removable for up to 6 months after application. This film can be printed, e.g. with your own logo or brand name.		0.08mm	0	1 roll (cut to desired roll widths)	
PROTECTIVE FOILS	The same of the sa	129323 PE protective tape with acrylic adhesive. This cleanly removable protective foil for indoor and outdoor applications provides excellent mechanical protection and is removable up to 2 months after application.	1360mm x 50mtr	0.13mm		1 roll (cut to desired roll widths)	
		FA12014 PVC protective tape with rubber adhesive layer. This removable protective tape for indoor applications gives good mechanical protection and is removable for up to 3 weeks after application.	1240mm x 33mtr	0.14mm	0	1 roll (cut to desired roll widths)	
		P515N Blue transparent PE protective film with acrylic adhesive layer. This protective foil for indoor and outdoor applications is suitable for protecting glass panes against dirt, dust, etc. and can be removed cleanly for up to 2 months after application.	1000mm x 100mtr	0.05mm	•	1 roll (cut to desired roll widths)	



Belgium
China
Denmark
Germany
Finland
France
India

Italy Mexico Netherlands Norway Poland Portugal Russia

Spain
Czech Republic
United Kingdom
United States of America
Sweden



STOKVIS TAPES BENELUX BV 21/05/2021

Belgium

Mechelsesteenweg 586C 1800 Vilvoorde Email: info@stokvistapes.be Tel. +32 (0)22 55 06 11

Netherlands

Van Hennaertweg 10 2952CA Alblasserdam Email: info@stokvistapes.nl Tel. +31 (0)78 699 21 00