

10 essentials Aerospace



Carpet tape (textile backing)

High performance, flame retardant double coated cloth backed tape. Highly conformable carpet installation tape that meets both Airbus and Boeing specifications. Good adhesion of carpet to walls or floor.

Type	Specification
P55	BMS 5-133D Type II, Class I / ABS 5648A FAR 25.583
K108	BMS 5-133D



Carpet tape (light weight)

Double sided, differentially coated tape with one clean peel removable side and one very high adhering side. Lighter than standard cloth carpet tapes because of polyester backing.

Type	Specification
1111	BMS 5-133G type IV class 1 FAR 25.583
2318B	AIMS-10-05-14



Cargo liner tape

Seam sealing and repair of cargo compartment liners. For use on covering pins/rivets where high adhesion and flame resistance is critical. Resists flame penetration. High tensile strength. Conformable backing accommodates angles and turns.

Type	Specification
K296FR	BMS 5-146 / ABD0031 FAR 25.583
P629	BMS 5-146 Type I, Class I



Cable harness tape

Single sided tape consist of a PTFE film carrier and a cured silicone adhesive. Very good resistance to ageing, and temperature. Resistant to almost all chemicals. The PTFE carrier provides a low coefficient of friction.

Type	Specification
P422	BAC 5034 Type IV, UL-510 ASTM D2686/ CID-A-A-59474A



Moisture barrier filmtape

Single sided tape for floor joint sealing on aircraft decking in all wet areas. Surface protection and sound dampening. Helps prevent corrosion and is flame retardant.

Type	Specification
P306	BMS 58-4118-0306
D9100SW	AIMS 10-05-004 / BMS 8-346C FAR 25.583



High speed tape

Dead soft aluminum foil tape with a high performance acrylic adhesive permits clean and easy tape removal, with no residue. Makes a vapor-tight seal that effectively combats moisture, contamination and corrosion. Easy to handle and easy to apply.

Type	Specification
P11	Airbus ABS 5604 A, Boeing BAC555, BAC5986, BAC5332, BAC5034 IV, Class 3A



Carpet protection tape

Single sided tape consisting of a modified Polyethylene carrier and a solvent based acrylic adhesive. It has a low enough adhesion to provide clean removability, but good enough adhesion to remain on the surface. Very good resistance against weather.

Type	Specification
YC13007	-



Slipguard

This single sided tape consists of an embossed Polypropylene carrier and a solvent based modified acrylic adhesive. Good adhesion to both smooth and rough surfaces. For protection of all kind of floors. It's "anti-slip" properties increases the safety at the job site.

Type	Specification
4222	-



Aircraft removable surface protection tape

Clean removable Polyethylene film with acrylic adhesive. For general surface protection applications on various surfaces during general maintenance within aircraft interiors. Flame retardant, abrasion, moisture and solvent resistant.

Type	Specification
5565 FR	- FAR 25.583



Sound damping & sealing foam

Black, closed-cell, vinyl/nitrile blend foam which meets the stringent flammability and smoke testing requirements of the aerospace market. For floor panel mounting and isolation; seal between mating surfaces; sound dampening and cushioning.

Type	Specification
680-1468	BMS 8-283 Type I FAR 25.583

All tapes are available in various widths.

Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product.

Call +31 (0)78-6992100 or email info@stokvistapes.nl for more information.

Premium Maskingtape

Professional ultrathin masking tape made off strong and flexible rice paper (washi).

Razor-sharp edges for good paint lines, clean removable within 2 months.

Ideal for high quality indoor masking and painting without paint going underneath your tape.

UV- and temperature resistant up to 150°C.

info@stokvistapes.nl / tel. 078 699 21 00



Lightweight Carpet Tape

Double sided, differentially coated tape with permanent adhesive on the carpet site and a removable adhesive for clean peel of floor panels on the other side.

Free of antimony trioxide, bromide, and halogen.

Lightweight construction; approximately 65% lighter than standard cloth carpet tapes for reduced aircraft weight and greater fuel economy.

The tape is flame retardant.

Articlenumber: 1111

Certifications: FAA - FAR 25.853 (a) , Boeing - BMS5-133G type IV class 1 , Airbus - ABD0031, Paragraph 7.3.2 and Paragraph 7.4

info@stokvistapes.nl / tel. 078 699 21 00

